SATCO | NUVO

Project / Job Name:

Location:

Fixture Type:

Notes:



S11902 - 3 Watt T5 LED; Miniature bi-pin base; 4000K; 50000 Average rated hours; 270 Lumens; 120-277 Volt; Type B; Ballast Bypass; Double Ended Wiring

DAMP LOCATION · ENCLOSED FIXTURE · CLASSIFIED cULus · FC · RoHS COMPLIANT · 50,000 HOURS · TYPE B · 5 YEAR WARRANTY · 120-277V · NSF

GENERAL

Company	SATCO
EA Height	9.0
EA Width	0.9
EA Length	0.9
Lamp Ballast Type AB	Type B
Ballasting Requirements	No ballast or external driver required
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Status	Active
Style	Utility
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Replaces F6T5/CW lamps
Amps	0.025-0.011A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Nominal Length	9.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Product Technology	LED
Fluor Equiv	6W
Incandescent Equivalent	25W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	240
Color Temp	Cool White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-13F to +113F (-25C to +45C)
Lumens	270L
Volts	120V-277V
Watts	3W

PHYSICAL

Lamp Base	Miniature Bi Pin
Finish	Frost
ANSI Base	G5
Lamp Type	T5
MOD Lamps	0.83
MOL	8.91

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures. Direct wire 120-277V line voltage; Double ended wiring
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923119026
Case Cube	1.8345
Case Height	22.83
Case Length	11.02
Case Quantity	200
Case UPC	10045923119023
Case Weight	12.8
Case Width	12.6
EA Cube	0.0042
EA Height	9.0
EA Length	0.9
EA Quantity	1
EA Weight	0.12
EA Width	0.9
Inner Cube	0.0945
Inner Height	11.0
Inner Length	2.8
Inner Quantity	10
Inner UPC	20045923119020
Inner Weight	1.4
Inner Width	5.3
Pack Type	Box
Web Length	8.91
Web Width	0.83

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, ETLus - Sanitation Recognized Component
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026