Project / Job Name:

Location:

Fixture Type:

Notes:



**S12130** - 5 Watt Mini LED; G9 Base; 3000K; Clear Finish; 120 Volt

## GENERAL

| | |
|---|---|
| Company | SATCO |
| EA Height | 4.84 |
| EA Width | 0.75 |
| EA Length | 3.27 |
| Candle Power | 40.0 |
| Lamp Filament | LED |
| Material | Ceramic / Polycarbonate (PC) |
| Fixture Type | Miniature |
| Status | Active |
| Style | Utility |
| Surge Protection | Built-in surge protection - 1.5KV |
| Total Harmonic Distortion | 70% |
| CCT Selectable | No |
| Wattage Selectable | No |
| Finish Family | Clear |
| Additional Info | Housing Material: Ceramic; Lens Material: Polycarbonate (PC) |
| Amps | 0.042A |
| Has Camera | No |
| IOT Enabled | No |
| Power Factor | 0.9 |
| SDS Class | LED_Lamp |
| Indoor Outdoor | Indoor |
| Product Technology | LED |
| Incandescent Equivalent | 40W |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 3000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 25000 |
| Beam Angle (degree) | 300 |
| Color Temp | Soft White |
| CRI | 80+ |
| Dimming Type | 120V only, Phase Cut (TRIAC) |
| Operating Frequency | 60Hz |
| Operating Temp | -4F to +104F (-20C to +40C) |
| Lumens | 550L |
| Volts | 120v |
| Watts | 5W |

## PHYSICAL

| | |
|---|---|
| Lamp Base | G9 Double Loop |
| Finish | Clear |
| Housing Color | White |
| ANSI Base | G9 |
| Lamp Type | T4 |
| MOD Lamps | 0.75 |
| MOL | 2.17 |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 5-Years |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | No |

## PACKAGING

| | |
|---|---|
| UPC | 045923121302 |
| Case Cube | 0.666 |
| Case Height | 12.13 |
| Case Length | 10.04 |
| Case Quantity | 48 |
| Case UPC | 10045923121309 |
| Case Weight | 4.92 |
| Case Width | 9.45 |
| EA Cube | 0.0069 |
| EA Height | 4.84 |
| EA Length | 3.27 |
| EA Quantity | 1 |
| EA Weight | 0.08 |
| EA Width | 0.75 |
| Inner Cube | 0.1342 |
| Inner Height | 5.63 |
| Inner Length | 8.86 |
| Inner Quantity | 12 |
| Inner UPC | 20045923121306 |
| Inner Weight | 1.07 |
| Inner Width | 4.65 |
| Pack Type | Carded |
| Web Length | 2.17 |
| Web Width | 0.75 |

## COMPLIANCE

| | |
|---|---|
| FCC Compliant | Yes |
| Location Rating | Damp |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Certified, cULus - Listed |
| California Ban | Lawful for sale |
| DLC Approved | No |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |



© Satco Products, Inc.
All rights reserved 2026