SATCO | NUVO



Project / Job Name:

Location:

Fixture Type:

Notes:

S15226 - 15/11/8/5 Watt A19 LED;
27K/30K/35K/40K/50K/65K 80 CRI; Medium Base;
Dimmable; 120 Volt

DAMP LOCATION · DIMMABLE · ENCLOSED FIXTURE · c UL us LISTED · FC · RoHS COMPLIANT · CCT SELECTABLE · 25,000 HOURS · 3 YEAR WARRANTY · 120 VOLT

GENERAL

Company	SATCO
EA Height	4.72
EA Width	2.36
EA Length	2.36
Lamp Filament	LED
Material	Plastic
Fixture Type	Type A
Status	Active
Surge Protection	Built-in-surge protection - 0.5KV
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	White
Additional Info	Default Wattage: 15W
Amps	0.165A
Operating Position	Universal
Power Factor	>0.7
SDS Class	LED_Lamp
Shatter Proof Type	Polycarbonate
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	100W/75W/60W/40W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K/6500K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	180
Color Temp	Warm White to Daylight
CRI	80+
Dimming Type	Linear Dimming, Phase cut
Operating Frequency	50/60Hz
Operating Temp	-13F to +113F (-25C to +45C)
Lumens	1500L/1100L/800L/450L
Volts	120v
Watts	15W/11W/8W/5W
Max Lumens	1500L

PHYSICAL

Lamp Base	Medium
Finish	Frost
ANSI Base	E26
Lamp Type	A19
MOD Lamps	2.38
MOL	4.61

ADDITIONAL INFO

Warranty	3-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923152269
Case Cube	0.5478
Case Height	10.83
Case Length	10.83
Case Quantity	24
Case UPC	10045923152266
Case Weight	5.31
Case Width	8.07
EA Cube	0.0152
EA Height	4.72
EA Length	2.36
EA Quantity	1
EA Weight	0.17
EA Width	2.36
Inner Cube	0.1135
Inner Height	5.12
Inner Length	7.48
Inner Quantity	6
Inner UPC	20045923152263
Inner Weight	1.16
Inner Width	5.12
Pack Type	Color Box
Web Length	4.61
Web Width	2.38

COMPLIANCE

CA Prop 65	Lead
Dark Sky Rated	No
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Non-Compliant
Title 20	No
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026