SATCO | NUVO

Project / Job Name:

Location:

Fixture Type:

Notes:



S18404 - 4.5 Watt LED PL 2-PIN; 5000K; 450 Lumens; G23 base; 50000 Average rated hours; 360 deg. Beam Angle; 120-277 Volt; Type B; Ballast Bypass

DAMP LOCATION · ENCLOSED FIXTURE · ETL CLASSIFIED Intertek · FC · RoHS COMPLIANT · 50,000 HOURS · TYPE B · 5 YEAR WARRANTY · 120-277V · IP 20

GENERAL

Company	SATCO
EA Height	6.89
EA Width	0.98
EA Length	1.46
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Plastic
Fixture Type	PL
Status	Discontinued
Style	Transitional
Surge Protection	Built-in-surge protection - 0.5KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.038-0.016A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Plastic (PS)
Lensed	Yes
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	5W/7W/9W
Incandescent Equivalent	40W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	360
Color Temp	Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-13F to +113F (-25C to +45C)
Lumens	450L
Volts	120V-277V
Watts	4.5W

PHYSICAL

Lamp Base	G23 (2-Pin)
Finish	Frost
Housing Color	White
ANSI Base	G23
Lamp Type	PL
MOD Lamps	1.3
MOL	6.54

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923184048
Case Cube	0.5317
Case Height	8.5
Case Length	17.72
Case Quantity	50
Case UPC	10045923184045
Case Weight	5.7
Case Width	6.1
EA Cube	0.0057
EA Height	6.89
EA Length	1.46
EA Quantity	1
EA Weight	0.11
EA Width	0.98
Inner Cube	0.0762
Inner Height	7.48
Inner Length	5.32
Inner Quantity	10
Inner UPC	20045923184042
Inner Weight	1.21
Inner Width	3.31
Pack Type	Box
Web Length	6.54
Web Width	1.3

COMPLIANCE

FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cETLus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026