SATCO | NUVO



Project / Job Name:

Location:

Fixture Type:

Notes:

S21760 - 10 Watt T8 LED; 24-Inch; 30K/35K/40K/50K/65K CCT Selectable; G13 Base; Ballast Type A/B; Frost Finish; 120-277 Ranged Voltage; Glass with PET Coating

GENERAL

Company	SATCO
EA Height	1.0
EA Width	1.0
EA Length	24.65
Lamp Ballast Type AB	Type A/B
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Status	Active
Style	Utility
Total Harmonic Distortion	20%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.083-0.036A
Has Camera	No
IOT Enabled	No
Nominal Length	24.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	15W/17W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	3000K/3500K/4000K/5000K/6500K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	170
Color Temp	Soft White to Daylight
CRI	80+
Dimming Type	Check Ballast MFG for Dimmer Compatibility, Only in Type A mode
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1450L
Volts	120V-277V
Watts	10W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Frost
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	24.65

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923217609
Case Cube	0.4815
Case Height	5.75
Case Length	24.65
Case Quantity	25
Case UPC	10045923217606
Case Weight	7.61
Case Width	5.87
EA Cube	0.0143
EA Height	1.0
EA Length	24.65
EA Quantity	1
EA Weight	0.29
EA Width	1.0
Pack Type	Sleeve
Web Length	24.65
Web Width	1.0

COMPLIANCE

DLC ID	S-KYQNVV
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026