SATCO | NUVO



Project / Job Name:

Location:

Fixture Type:

Notes:

**S23142** - 54/45/36 Wattage Selectable; LED HID Replacement; CCT Selectable; Type B; Ballast Bypass; Extended Mogul base; 120-277 Volt; ColorQuick Technology; PowerQuick Technology

DAMP LOCATION · DIMMABLE · ENCLOSED FIXTURE · CLASSIFIED cULus · cULus LISTED · FC · RoHS COMPLIANT · CCT SELECTABLE · 50,000 HOURS · TYPE B · 5 YEAR WARRANTY · 120-277V

## GENERAL

| | |
|---|---|
| Company | SATCO |
| EA Height | 3.66 |
| EA Width | 3.66 |
| EA Length | 10.98 |
| Lamp Ballast Type AB | Type B |
| Ballasting Requirements | Ballast Bypass |
| Lamp Filament | LED |
| Material | Plastic (PS) |
| Fixture Type | Corncob |
| Status | Active |
| Style | Contemporary |
| Surge Protection | Built-in surge protection - 4KV |
| Total Harmonic Distortion | 16.60% |
| CCT Selectable | Yes |
| Wattage Selectable | Yes |
| Finish Family | White |
| Additional Info | Safety cable provided with S23143, S23144, S23145 ONLY and is required upon installation of these high bay, base-up applications. (Please See Instructions) |
| Amps | 0.540-0.195/0.450-0.162/0.360-0.130A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Material | Plastic |
| Minimum Compartment Size | Length: 7.88 in. Width: 7.88 in. |
| Operating Position | Universal |
| Power Factor | >0.9 |
| SDS Class | LED_Lamp |
| Indoor Outdoor | Indoor, Outdoor |
| Product Technology | LED |
| Incandescent Equivalent | 125W/150W/200W |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 3000K/4000K/5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 300 |
| Color Temp | Warm to Cool White |
| CRI | 80+ |
| Dimming Type | Only dimmable through wattage selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls., Step Dimming |
| Operating Frequency | 50-60Hz |
| Operating Temp | -40F to +140F (-40C to +60C) |
| HID Equivalent | 200W/175W/150W |
| Lumens | 7560L/6300L/5040L |
| Volts | 120V-277V |
| Watts | 54W/45W/36W |
| Max Lumens | 7560L |

## PHYSICAL

| | |
|---|---|
| Lamp Base | Mogul Extended |
| Finish | WHITE |
| Housing Color | Dark Gray |
| ANSI Base | EX39 |
| Lamp Type | Corncob |
| MOD Lamps | 3.35 |
| MOL | 9.69 |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 5-Years |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes |

## PACKAGING

| | |
|---|---|
| UPC | 045923231421 |
| Case Cube | 1.4885 |
| Case Height | 12.52 |
| Case Length | 16.73 |
| Case Quantity | 12 |
| Case UPC | 10045923231428 |
| Case Weight | 27.3 |
| Case Width | 12.28 |
| EA Cube | 0.0851 |
| EA Height | 3.66 |
| EA Length | 10.98 |
| EA Quantity | 1 |
| EA Weight | 2.02 |
| EA Width | 3.66 |
| Inner Cube | 0.6143 |
| Inner Height | 11.57 |
| Inner Length | 11.54 |
| Inner Quantity | 6 |
| Inner UPC | 20045923231425 |
| Inner Weight | 12.91 |
| Inner Width | 7.95 |
| Pack Type | Box |
| Web Length | 9.69 |
| Web Width | 3.35 |

## COMPLIANCE

| | |
|---|---|
| Bug Rating | B2-U5-G3 |
| DLC ID | S-KS5HW0 |
| FCC Compliant | Yes |
| Location Rating | Damp |
| NSF Approved | No |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Certified, cULus - Classified, cULus - Listed |
| California Ban | Lawful for sale |
| DLC Approved | Yes |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |



© Satco Products, Inc.
All rights reserved 2026