Project / Job Name:

Location:

Fixture Type:

Notes:

**S28562** - 10 Watt; A19 LED; Frosted; 4000K; Medium base; 120 Volt; 4-pack

## GENERAL

| | |
|---|---|
| Company | SATCO |
| EA Height | 4.53 |
| EA Width | 2.48 |
| EA Length | 9.84 |
| Lamp Filament | LED |
| Material | Plastic |
| Fixture Type | Type A |
| Status | Discontinued |
| Style | Traditional |
| CCT Selectable | No |
| Wattage Selectable | No |
| Finish Family | White |
| Amps | 0.083A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Frost |
| Lensed | Yes |
| Operating Position | Universal |
| Power Factor | 0.81 |
| SDS Class | LED_Lamp |
| Indoor Outdoor | Indoor |
| Product Technology | LED |
| Incandescent Equivalent | 60W |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 4000K |
| Dimmable | Non-Dimmable |
| Hours Rated | 15000 |
| Beam Angle (degree) | 220 |
| Color Temp | Cool White |
| CRI | 90+ |
| Operating Frequency | 60Hz |
| Operating Temp | -13F to +113F (-25C to +45C) |
| Lumens | 800L |
| Volts | 120v |
| Watts | 10W |

## PHYSICAL

| | |
|---|---|
| Lamp Base | Medium |
| Finish | Frost |
| Housing Color | White |
| ANSI Base | E26 |
| Lamp Type | A19 |
| MOD Lamps | 2.362 |
| MOL | 4.331 |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 2-Years |
| Rated For Enclosed Fixture | Yes |

## PACKAGING

| | |
|---|---|
| UPC | 045923285622 |
| Case Cube | 0.9617 |
| Case Height | 10.04 |
| Case Length | 15.87 |
| Case Quantity | 12 |
| Case UPC | 10045923285629 |
| Case Weight | 7.72 |
| Case Width | 10.43 |
| EA Cube | 0.064 |
| EA Height | 4.53 |
| EA Length | 9.84 |
| EA Quantity | 1 |
| EA Weight | 0.61 |
| EA Width | 2.48 |
| Pack Type | Box |
| Web Length | 4.331 |
| Web Width | 2.362 |

## COMPLIANCE

| | |
|---|---|
| FCC Compliant | Yes |
| Location Rating | Damp |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Certified, cULus - Listed |
| California Ban | Lawful for sale |
| DLC Approved | No |
| Title 20 | Yes |
| T24/JA8 Compliant | No |



© Satco Products, Inc.
All rights reserved 2026