SATCO | NUVO



Project / Job Name:

Location:

Fixture Type:

Notes:

S39769 - 75 Watt LED HID Replacement; 5000K; Mogul Extended base; Adjustable Beam Angle; Type B Ballast Bypass;120-277 Volt

DAMP LOCATION · ENCLOSED FIXTURE · CLASSIFIED cULus · cULus LISTED · FC · RoHS COMPLIANT · 50,000 HOURS · TYPE B · 5 YEAR WARRANTY · 120-277V

GENERAL

Company	SATCO
EA Height	4.96
EA Width	10.16
EA Length	4.96
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Aluminum / Steel / Thermo Plastic (PBT)
Fixture Type	LED HID
Product Notes	Closed 260 deg; Partial 150 deg; Open 120 deg
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 4KV
Total Harmonic Distortion	<20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	Clear
Additional Info	PIR Sensor available as an accessory
Amps	0.750-0.271A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Thermo Plastic (PBT)
Lensed	Yes
Minimum Compartment Size	Width: 9.30 in. Depth: 9.30 in. Height: 10.50 in.
Operating Position	Base Up or Down
Photo Cell	Optional Add-On
Power Factor	>0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	105W
Incandescent Equivalent	750W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	120/150/260
Color Temp	Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +149F (-20C to +65C)
HID Equivalent	400W
Lumens	10500L
Volts	120V-277V
Watts	75W

PHYSICAL

Lamp Base	Mogul Extended
Finish	Clear
Housing Color	White
ANSI Base	EX39
Lamp Type	Corncob
MOD Lamps	4.08
MOL	8.46

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923397691
Case Cube	2.5429
Case Height	11.81
Case Length	22.24
Case Quantity	12
Case UPC	10045923397698
Case Weight	35.9
Case Width	16.73
EA Cube	0.1446
EA Height	4.96
EA Length	4.96
EA Quantity	1
EA Weight	3.11
EA Width	10.16
Inner Cube	1.0002
Inner Height	10.63
Inner Length	15.47
Inner Quantity	6
Inner UPC	20045923397695
Inner Weight	17.1
Inner Width	10.51
Pack Type	Box
Web Length	8.46
Web Width	4.08

COMPLIANCE

FCC Compliant	Yes
IP Rating	IP64
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026