SATCO | NUVO



Project / Job Name:

Location:

Fixture Type:

Notes:

S39798 - 40 Watt LED HID Replacement; 2700K; Mogul extended base; Adjustable Beam Angle; Type B Ballast Bypass;100-277 Volt

DAMP LOCATION | ENCLOSED FIXTURE | CLASSIFIED cULus | cULus LISTED | FC | RoHS COMPLIANT | 50,000 HOURS | TYPE B | 5 YEAR WARRANTY | 120-277V

GENERAL

Company	SATCO
EA Height	8.66
EA Width	4.65
EA Length	4.65
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Aluminum / Steel / Thermo Plastic (PBT)
Fixture Type	LED HID
Product Notes	Closed 260 deg; Partial 150 deg; Open 120 deg
Status	Discontinued
Style	Utility
Surge Protection	Built-in surge protection - 4KV
Total Harmonic Distortion	<20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	Clear
Additional Info	PIR Sensor available as an accessory
Amps	0.400-0.144A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Thermo Plastic (PBT)
Lensed	Yes
Minimum Compartment Size	Width: 8.00 in. Depth: 8.00 in. Height: 11.00 in.
Operating Position	Base Up or Down
Photo Cell	Optional Add-On
Power Factor	>0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	65W
Incandescent Equivalent	300W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	2700K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	120/150/260
Color Temp	Warm White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +149F (-20C to +65C)
HID Equivalent	175W
Lumens	5120L
Volts	120V-277V
Watts	40W

PHYSICAL

Lamp Base	Mogul Extended
Finish	Clear
Housing Color	White
ANSI Base	EX39
Lamp Type	Corncob
MOD Lamps	3.31
MOL	7.24

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923397981
Case Cube	1.9843
Case Height	10.24
Case Length	21.26
Case Quantity	12
Case UPC	10045923397988
Case Weight	23.8
Case Width	15.75
EA Cube	0.1084
EA Height	8.66
EA Length	4.65
EA Quantity	1
EA Weight	2.17
EA Width	4.65
Inner Cube	0.7585
Inner Height	9.13
Inner Length	14.53
Inner Quantity	6
Inner UPC	20045923397985
Inner Weight	11.2
Inner Width	9.88
Pack Type	Box
Web Length	7.24
Web Width	3.31

COMPLIANCE

FCC Compliant	Yes
IP Rating	IP64
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026