SATCO | NUVO



Project / Job Name:

Location:

Fixture Type:

Notes:

S39901 - 9 Watt T8 LED; 2Ft; 3500K; Medium Bi Pin base; 50000 Average rated hours; 1100 Lumens; Type B; Ballast Bypass; Single or Double Ended Wiring

GENERAL

Company	SATCO
EA Height	1.1
EA Width	1.1
EA Length	24.0
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Product Notes	Built-in shock resistant circuit - (not hot until both ends are installed)
Status	Active
Style	Utility
Total Harmonic Distortion	20%
Tube Guard Use	Yes
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Equivalent CCT selectable option available in S11764
Amps	0.075-0.032A
Has Camera	No
IOT Enabled	No
Lens Finish	Gloss White
Lens Material	Glass
Nominal Length	24.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	17W
Incandescent Equivalent	40W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	3500K
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Neutral White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1100L
Volts	120V-277V
Watts	9W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Gloss White
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.1
MOL	23.78

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923399015
Case Cube	0.5208
Case Height	6.0
Case Length	25.0
Case Quantity	25
Case UPC	10045923399012
Case Weight	6.88
Case Width	6.0
EA Cube	0.0168
EA Height	1.1
EA Length	24.0
EA Quantity	1
EA Weight	0.28
EA Width	1.1
Pack Type	Sleeve
Web Length	23.78
Web Width	1.1

COMPLIANCE

DLC ID	PLSLJY8NLUXI
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026