SATCO | NUVO



Project / Job Name:

Location:

Fixture Type:

Notes:

S49391 - 22 Watt LED HID Replacement; 80 CRI; 5000K; Type B; Ballast Bypass; Medium base; Economy Hi-Pro

DAMP LOCATION | ENCLOSED FIXTURE | CLASSIFIED cULus | cULus LISTED | FC | RoHS COMPLIANT | 35,000 HOURS | TYPE B | 3 YEAR WARRANTY | 120-277V | IP 65

GENERAL

Company	SATCO
EA Height	7.28
EA Width	2.87
EA Length	2.87
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Aluminum / Polycarbonate (PC)
Fixture Type	LED HID
Status	Active
Style	Contemporary
Surge Protection	Built-in surge protection - 2KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Safety cable provided with S49395, S49396, S49397, S49675, S49676, S49677 ONLY and is required upon installation of these high bay, base-up applications. (Please See Instructions)
Amps	0.220-0.079A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Polycarbonate (PC)
Minimum Compartment Size	Length: 6 in. Width: 6 in. Height: 8.5 in.
Operating Position	Universal
Photo Cell	No
Power Factor	>0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Incandescent Equivalent	150W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	35000
Beam Angle (degree)	300
Color Temp	Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-13F to +131F (-25C to +55C)
HID Equivalent	100W
Lumens	3036L
Volts	120V-277V
Watts	22W

PHYSICAL

Lamp Base	Medium
Finish	WHITE
Housing Color	White
ANSI Base	E26
Lamp Type	Corncob
MOD Lamps	2.39
MOL	5.71

ADDITIONAL INFO

Warranty	3-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923493911
Case Cube	1.2658
Case Height	8.98
Case Length	19.21
Case Quantity	24
Case UPC	10045923493918
Case Weight	20.28
Case Width	12.68
EA Cube	0.0347
EA Height	7.28
EA Length	2.87
EA Quantity	1
EA Weight	0.85
EA Width	2.87
Inner Cube	0.5123
Inner Height	7.95
Inner Length	12.09
Inner Quantity	12
Inner UPC	20045923493915
Inner Weight	9.7
Inner Width	9.21
Pack Type	Box
Web Length	5.71
Web Width	2.39

COMPLIANCE

FCC Compliant	Yes
IP Rating	IP65
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026