SATCO | NUVO



Project / Job Name:

Location:

Fixture Type:

Notes:

**S49673** - 45 Watt LED HID Replacement; 4000K; Extended Mogul base; Type B Ballast Bypass; Economy Hi-Pro

DAMP LOCATION | ENCLOSED FIXTURE | CLASSIFIED cULus | cULus LISTED | FC | RoHS COMPLIANT | 35,000 HOURS | TYPE B | 3 YEAR WARRANTY | 120-277V | IP 65

## GENERAL

| | |
|---|---|
| Company | SATCO |
| EA Height | 9.06 |
| EA Width | 3.94 |
| EA Length | 3.94 |
| Lamp Ballast Type AB | Type B |
| Ballasting Requirements | Ballast Bypass |
| Lamp Filament | LED |
| Material | Aluminum / Polycarbonate (PC) |
| Fixture Type | LED HID |
| Status | Active |
| Style | Contemporary |
| Surge Protection | Built-in surge protection - 3KV |
| CCT Selectable | No |
| Wattage Selectable | No |
| Finish Family | White |
| Additional Info | Safety cable provided with S49395, S49396, S49397, S49675, S49676, S49677 ONLY and is required upon installation of these high bay, base-up applications. (Please See Instructions) |
| Amps | 0.450-0.162A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Clear |
| Lens Material | Polycarbonate (PC) |
| Minimum Compartment Size | Length: 8 in. Width: 8 in. Height: 11 in. |
| Operating Position | Universal |
| Photo Cell | No |
| Power Factor | >0.9 |
| SDS Class | LED_Lamp |
| Indoor Outdoor | Indoor, Outdoor |
| Product Technology | LED |
| Incandescent Equivalent | 300W |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 4000K |
| Dimmable | Non-Dimmable |
| Hours Rated | 35000 |
| Beam Angle (degree) | 300 |
| Color Temp | Cool White |
| CRI | 80+ |
| Operating Frequency | 50/60Hz |
| Operating Temp | -13F to +131F (-25C to +55C) |
| HID Equivalent | 175W |
| Lumens | 6165L |
| Volts | 120V-277V |
| Watts | 45W |

## PHYSICAL

| | |
|---|---|
| Lamp Base | Mogul Extended |
| Finish | WHITE |
| Housing Color | White |
| ANSI Base | EX39 |
| Lamp Type | Corncob |
| MOD Lamps | 3.35 |
| MOL | 8.06 |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 3-Years |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes |

## PACKAGING

| | |
|---|---|
| UPC | 045923496738 |
| Case Cube | 1.1538 |
| Case Height | 9.84 |
| Case Length | 16.34 |
| Case Quantity | 12 |
| Case UPC | 10045923496735 |
| Case Weight | 21.38 |
| Case Width | 12.4 |
| EA Cube | 0.0814 |
| EA Height | 9.06 |
| EA Length | 3.94 |
| EA Quantity | 1 |
| EA Weight | 1.78 |
| EA Width | 3.94 |
| Pack Type | Box |
| Web Length | 8.06 |
| Web Width | 3.35 |

## COMPLIANCE

| | |
|---|---|
| FCC Compliant | Yes |
| IP Rating | IP65 |
| Location Rating | Damp |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Certified, cULus - Classified, cULus - Listed |
| California Ban | Lawful for sale |
| DLC Approved | No |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |



© Satco Products, Inc.
All rights reserved 2026