Project / Job Name:

Location:

Fixture Type:

Notes:



S8475 - 28 Watt; T8; U-Bend Fluorescent; 6500K Daylight; 85 CRI; Medium Bi Pin base

GENERAL

Company	SATCO
EA Height	7.13
EA Width	23.0
EA Length	1.13
Lamp Ballast Type AB	Type A
Ballasting Requirements	For use with Electronic ballasts
Fixture Type	U-Bend
Hg Content	9.0
Status	Discontinued
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Has Camera	No
IOT Enabled	No
Leg Spacing	6.0
Lens Finish	White
Lensed	Yes
Mean Lumens	2350
Nominal Length	22.5
Operating Position	Universal
SDS Class	Linear_Fluorescent_Lamp
Product Technology	Fluorescent
Start Method	Instant Start
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	6500K
Dimmable	Non-Dimmable
Hours Rated	20000
Beam Angle (degree)	360
Color Temp	Daylight
CRI	85+
Operating Temp	Ballast Dependent
Lumens	2500L
Watts	28W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	WHITE
Housing Color	None
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	22.5

ADDITIONAL INFO

Warranty	3-Years

PACKAGING

UPC	045923084751
Case Cube	2.094
Case Height	10.24
Case Length	23.62
Case Quantity	16
Case UPC	10045923084758
Case Weight	15.18
Case Width	14.96
EA Cube	0.1072
EA Height	7.13
EA Length	1.13
EA Quantity	1
EA Weight	0.85
EA Width	23.0
Pack Type	Box
Web Length	22.5
Web Width	1.0

COMPLIANCE

ROHS Compliant	Yes
Safety Listing	Not Applicable
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24/JA8 Compliant	No
US State Ban	CA, CO, HI, ME, MN, OR, RI, VT

© Satco Products, Inc.
All rights reserved 2026