Project / Job Name:

Location:

Fixture Type:

Notes:

S8750 - 8 Watt LED PL; GU24 Base; 27K/30K/35K/40K/50K CCT Selectable; Type B Ballast Bypass; 120-277 Volt



GENERAL

Company	SATCO
EA Height	7.28
EA Width	1.65
EA Length	1.65
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Candle Power	200.0
Lamp Filament	LED
Material	Plastic
Fixture Type	PL
Status	Active
Style	Transitional
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	<20%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.070A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	18W
Incandescent Equivalent	60W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Warm White to Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	950L/975L/1000L/1050L/1050L
Volts	120V-277V
Watts	8W
Max Lumens	1050L

PHYSICAL

Lamp Base	Bi Pin GU24
Finish	Frost
Housing Color	White
ANSI Base	GU24
Lamp Type	PL
MOD Lamps	1.38
MOL	6.5

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923087509
Case Cube	0.9563
Case Height	9.06
Case Length	18.9
Case Quantity	50
Case UPC	10045923087506
Case Weight	14.33
Case Width	9.65
EA Cube	0.0115
EA Height	7.28
EA Length	1.65
EA Quantity	1
EA Weight	0.3
EA Width	1.65
Inner Cube	0.1461
Inner Height	7.87
Inner Length	9.06
Inner Quantity	10
Inner UPC	20045923087503
Inner Weight	0.3
Inner Width	3.54
Pack Type	Box
Web Length	6.5
Web Width	1.38

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24/JA8 Compliant	No
US State Ban	CA

© Satco Products, Inc.
All rights reserved 2026